



ITEM 項目	PARTS NAME 零件名稱	Q'TY 數量	MATERIAL 材質	FINISH/REMARK 處理/備註
1	HOUSING	1	P.B.T+G.F	UL-94V-0 (Block)
2	CONTACT	16	Phosphor Bronze	Gold flash selective

NOTES

- MATERIAL: See drawing
- ELECTRICAL
 - Insulator resistance: 1000M ohms Min. @ 250 VDC
 - Withstanding voltage: 100 VAC / minute
 - Contact resistance: 50m ohms Max.
- MECHANICAL
 - Mating force: 30N(3.06kgf) Max.
 - Unmating force: 4.2N(0.43kgf) Min.
 - Durability: 10000 cycles Min.
 - Contact retention force: 4.2N(0.43kgf) Min
- PACKING: 500pcs/bag (reference)
- PART NO.

M30	-	336	-	0	0	01
SERIES		Connector		MATERIAL TYPE		TYPE NO.
MODEL NO.	336					01=Type 1
						PROCESS NO. "0"
						MATERIAL TYPE
						0=semi-finished goods

CYPRESS INDUSTRIES

A	EXXXX-XXX	△ X 0					UNLESS OTHERWISE SPECIFIED TOLERANCE 尺寸公差 X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±5°00'	CHECKED 日期 03/28/02 工程師	DESIGNED 日期 H.T.CHEN 03/28/02'	SCALE 比例 4/1 SIZE 尺寸 A3	TITLE 產品名稱 ASS'Y HOUSING SMD type-16 position	PART NO. 產品編號 M30-336-0001	REV. 版本 A
	REV. 版本	EDN NO. 訂製號碼	MARK 記號	REVISIONS 改裝內容	SIGN 簽名	DATE 日期					DOC. NO. 文件編號 CUT-336-001		