

NOTE:

1. CABLE: 30AWG,UL20276,AL+B-FOIL, [(#30*1P+D+FAM)*4PCS+#30*1P+#28*5C]+AM+B, BLACK COLOR,OD=7.0mm,PVC JACKET.

2. LENGTH: 3000mm

3. CONNECTORS: HDMI(M)*1PCS(BLACK INSULATOR), DVI(24+1)P*1PCS(BLACK INSULATOR)(全为镀金壳)(Gold pin& shell)

4. MOLD: 成型模--裝配模

5. SCREW: #4*40 INCH SCREW*2PCS,

6. CONTACTS:

HDMI(M)	1	3	2	4	6	5	7	9	8	10	12	11	17	18	15	16	19	64
DVI(24+1)P	2	1,	3	10	9	11	18	17	19	23	24	22	15	14	.6	7	16	64
	對絞		地	對絞 地		ᅖ	對絞		地	對絞		地	30AWG		_2	28AWG		

7. OPEN/SHORT TEST: 100% TEST. INSULATION: MIN. 2M.

COMPANY	CYF	PRESS	ITEM NO.	DV-HDV-GD-3M	NO B			
REVISION	DATE	DISCRIPTION	DRAWN BY		CHDMIDVI03FGBK			
REV.A/0	2006.11.16	S	DESIGNED BY		Copper Cable DVI Male, Gol	d Plated, 03F1		
			APPROVAL		(1000mm), Bla	CK, ROHS		

